THE NEWEST ZAPAK ZP-CT32A

Battery Cord Strap Tensioner





Specification

- > Strap Type: Composite & Woven cord strapping
- > Strap Width: 19 32mm; Thickness: 0.85~1.65mm
- > Tensioning Force: 6 settings (300 800 daN)
- Tensioning Speed: 35 mm/s
- Weight including battery: approx. 3.6 kg

Safety

- Single-handed operation conforms to CE safety directive and meets RoHS requirements.
- Li-lon battery complies with UN38.3 safety requirements.





Latest technology

- ➤ Brushless Motor Zapak's latest 4th generation Brushless Motor generates a very steady output to ensure consistent and reliable tensioning for your cord strapping needs.
- Bosch 18V 4.0Ah Li-Ion Battery rechargeable battery with Charge Level Indicator (CLI), can strap up to 350 cycles per fully charged battery.

Powerful & Reliable

- > Tensioning Force Max. Tension 800 daN.
- ➤ Industrial Grade Tool we are the original manufacturer of the ZP-CT32A. The tensioner is completely designed and newly molded for Industrial Grade use.
- ➤ The ZP-CT32A is NOT made by simply attaching a typical electric drill to a manual windlass tensioner.

Smart & Easy

- Electronic Control Unit (ECU) 3 pre-programmed tension modes: Auto/Semi/ Manual. And tension torque (1-6 levels) are electronically controlled (No need to hand turn a manual clutch to change torque).
- Designated Quick Reverse Button (QRB) pre-programmed auto reverse button allows for easy reverse turning of the windlass for quick tool removal after tension (without having to switch back and forth on the Forward/Reverse button on a typical electric drill).
- Cutter designed to cut both Composite and Woven cord straps.

Ergonomic

- 6 Degree Angle on the handle bar ergonomically designed to lessen wrist fatigue while tensioning on a flat surface, and during vertical operation.
- Low Center of Gravity design reduced the overall height of the tensioner to lessen operating fatigue during horizontal & vertical operation.

